Acrylic Putty

SMOOTH

MATT FINISH

METHOD OF APPLICATION
PUTTY KNIFE OR TROWEL

DILUTION: WATER (IF DESIRED)

DRYING TIME:
1-2 HOURS (AT 30°C & 65% RELATIVE HUMIDITY)

RECOAT TIME:
4-6 HOURS

COVERAGE: 35-40 SQ.FT/KG/CT
(AT 200 MICRONS THICKNESS)

SHADE: WHITE

PACKAGING:
20KG, 10KG, 5KG & 1KG

CRACK RESISTANT





Acrylic Putty is recommended as wall filler to be applied on wall plaster and masonries to fill the porosity of the surface and thereby reducing the absorption of the emulsion paints.

This product is recommended for both interior & exterior use.

- Water Based, ready-to-use putty meant for filling and smoothening out cracks and dents on the plastered wall or similar interior & exterior surfaces
- Special acrylic binders that ensure that it retains a strong grip on the wall surface, thereby increasing the life of the paint film
- Ensures smoothness and consistency
- On account of the putty's exceptional whiteness and smoothness, emulsions painted over the putty will tend to look richer
- Enhances breath ability and lesser porosity compared to conventional putty, thus improving paint performance further
- Quick drying, thus ensuring faster completion of jobs
- Better alkali resistance, thus making it more suitable for new wall

ACRYLIC PUTTY

