Water Tite

Waterproof Wall Putty

SMOOTH FINISH

METHOD OF APPLICATION
PUTTY KNIFE OR TROWEL

DILUTION: WATER

DRYING TIME:
6-8 HOURS (AT 30°C & 65% RELATIVE HUMIDITY)

RECOAT TIME:
4-6 HOURS

COVERAGE: 12-18 SQ.FT/KG
FOR UPTO 1.5 MM THICKNESS IN 2 COATS

SHADE: WHITE

PACKAGING:
40KG, 20KG, 5KG & 1KG





Jewell Watertite Waterproof Wall Putty is a premium quality powder putty that is specially designed with silicone and anti-efflorescence additives to give unique waterproofing properties and efflorescence resistance for a smooth finish and extended life to the top coats.

It is developed as a base coat to cover unevenness and pinholes in plastered surfaces and to make the walls/ceilings ready for painting.

It contains finest quality minerals, white cement, redispersible polymers and special additives to enhance the adhesion of putty to the surface & makes it suitable for application to both interior as well as exterior surfaces.

Water Repellency
Cured surface after waterproofing with wall putty provides excellent hydrophobicity, exhibiting “Lotus Bead” effect.

Anti-Efflorescent
Cured surface shows remarkably distinct anti-efflorescence effect in comparison to traditional powder putties.

Vibrant White Whiteness
Provides the best-in-class whiteness compared to normal white cement-based putties.

Waterproofing Warranty
Comes with 2-year waterproofing warranty on Dampness when used with Jewell Damproof Primer in Interiors.

Resists Peeling, Blistering & Cracking
Highly durable that resists hair line cracking

Aesthetic Finish
Seamless finish with pin holes filling capability & gives butter like smoothness.

Ease of Application
Mixed paste is light and no extra strength required for applying on wall.

WALL PUTTY RANGE

