White Primer

MATT FINISH

METHOD OF APPLICATION
BRUSH, ROLLER & SPRAY

DILUTION:
MINERAL TURPENTINE OIL

DRYING TIME:
SURFACE DRY 60 MIN /
HARD DRY 48 HOURS

RECOAT TIME:
AT AN INTERVAL OF 6-8 HOURS

COVERAGE: 140-180 SQ.FT/LTR/CT
COAT ON A WELL PREPARED SURFACE

SHADE: WHITE

PACKAGING:
20LTR, 10LTR, 4LTR, 1LTR,
500ML & 200ML

STAIN BLOCKER





- Superior Adhesion
- Superior Hiding
- Alkali Resistant
- Bright White Finish
- No Chalking

SOLVENTBORNE RANGE

JEWELL WHITE PRIMER is a solvent based primer that should be used only on interior surfaces. It can be applied on suitably prepared masonry and wall surfaces, as well as wooden surfaces like doors, windows, furniture, cabinets etc. It is an undercoat that provides superior adhesion to the surface, thereby increasing the life of the entire paint system.

It has excellent sealing properties, which leads to lower absorption, ensuring a uniform deposition of topcoats. It sets fast, has good healing properties, good resistance to wall alkalinity, moisture and fungus.

