

Interior Primer

MATT FINISH

METHOD OF APPLICATION

BRUSH, ROLLER & SPRAY

DILUTION: WATER

DRYING TIME:

SURFACE DRY 30 MINUTES /
HARD DRY 7DAYS

RECOAT TIME:

AT AN INTERVAL OF 2-4 HOURS

COVERAGE: 220-260 SQ.FT/L/CT

ON A WELL PREPARED SURFACE

SHADE: WHITE

PACKAGING:

20LTR, 10LTR, 4LTR & 1LTR



-  Low VOC
-  No Chalking
-  Solvent Free
-  Quick Drying
-  Excellent Binding
-  Good Hardness
-  Alkali Resistance
-  Excellent Coverage
-  Suppresses Stain Easily
-  Seals Dry Porous Surfaces
-  Excellent Adhesion to Substrate
-  No Added Lead, Mercury & Chromium

Jewell's Interior Primer is water thinnable wall primer, formulated by using copolymer emulsion and ideal combination of pigments and extenders, so as to ensure deep penetration and sealing of porous surfaces.

It provides good sealing property that ensures smooth deposition of the paint film. It is pigmented white to give reasonable opacity to the primer.

It is suitable in interior applications, for priming of plastered surfaces and other masonry works. It makes the surface less absorbent and is specially fortified with fungicides, thus providing good resistance to wall alkalinity, moisture and fungus.



PREMIUM RANGE