

Polymer Wall Putty

SMOOTH FINISH

METHOD OF APPLICATION:
PUTTY KNIFE OR TROWEL

DILUTION: WATER

DRYING TIME:
6-8 HOURS (AT 30°C & 65%
RELATIVE HUMIDITY)

RECOAT TIME:
4-6 HOURS

COVERAGE: 12 - 15 SQ.FT/KG
FOR UPTO 1.5 MM THICKNESS
IN 2 COATS

SHADE: WHITE

PACKAGING:
40KG, 20KG, 5KG & 1KG



"Jewell" Polymer Wall Putty is a specially designed product, manufactured with a new "Low DustTechnology" which makes a dramatic reduction in airborne dust, created during pouring and mixing of Putty without changing on white cement, redispersible polymer and functional additives for application on rough plasters to give a smoother finish & stronger adhesion. It is best suited to minimize paint cost and extend its durability.

It protects your expensive paint and retains its beauty for long. It reduces the repainting frequency, thus delivering a better life time value as advanced manufacturing process makes it better than other wall putty's due to its better water resistance, workability, smoothness and durability. Being pure white and smooth, it brings out the true tone/shade of expensive paint applied over it.

-  Applicable on both new and old wall surfaces
-  Gives a smooth finish
-  No curing required
-  Water resistant
-  Prevents water seepage/leakage through cracks/voids in mortar concrete
-  Non-toxic, odorless & antifungal
-  Good Tensile Strength, Compressive Strength & also Flexural Strength
-  Controlled water vapor permeability
-  Excellent Abrasion Resistance
-  Resists the growth of algae and fungi on wall
-  Good intercoat adhesion to Emulsion Paints
-  Reduction in airborne dust

WALL PUTTY RANGE

