

Anti-Rust PU Enamel

HI-GLOSS

METHOD OF APPLICATION

BRUSH, ROLLER & SPRAY

DILUTION:

MINERAL TURPENTINE OIL &
SOLVENT THINNER

DRYING TIME:

SURFACE DRY 3-4 HOURS /
HARD DRY 7 DAYS

RECOAT TIME:

AT AN INTERVAL OF 6-8 HOURS

COVERAGE: 185-225 SQ.FT/LTR/CT

COAT ON A WELL PREPARED
SURFACE

SHADE: WHITE, COLORS & BASES

PACKAGING:

20LTR, 10LTR, 4LTR, 1LTR,
500ML, 200ML, 100ML & 50ML



JEWELL ANTI-RUST PU ENAMEL is manufactured with suitable polyurethane resin, finest pigments and few important additives.

It gives mirror like gloss with tough film and everlasting finish. It is a highly washable paint, thus you can wipe off most common household stains easily.

JEWELL Anti-rust PU Enamel is solvent based liquid paint that can be used both for exterior and interior surfaces, mainly on mild steel, wooden and suitably prepared masonry surfaces.

-  Lasts Longer Than Ordinary Enamel
-  Interior & Exterior Durable
-  Outstanding Hiding
-  Excellent Gloss
-  Faster Drying Time
-  Better Clarity
-  Non Yellowing
-  Anti Fungal



SOLVENTBORNE RANGE