



▲ TOP COAT



 Upto 1mm
Crack Bridging

 High SPF
UV Block

 Advanced
Fungal Protection

20L



100% ACRYLIC
LATEX PAINT

FOR EXTERIOR



Rich Sheen
finish

JEWELL HELMET FLEX-N-SHINE

Engineered to Protect. Designed to Impress


Jewell Helmet Flex-n-Shine is a 100% acrylic latex exterior Emulsion powered by PU ELIXIR Technology, forming a flexible elastomeric film that bridges hairline cracks up to 1 mm and protects against moisture damage. Its Anti-Soiling

Technology resists dust and pollutants, while superior UV, algae, and fungal resistance ensures long-lasting colour and sheen. With a rich premium finish and GreenPro-certified low VOC formula, it delivers durable, safer, global-grade exterior protection.

ADVANTAGES

-  Green Pro Certified
-  Stretchable Elastomeric Paint
-  Upto 1mm Crack Bridging
-  High SPF UV Block
-  Advanced Fungal Protection
-  Anti-Soiling Protection
-  Dust & Algae Resistance
-  Rich Sheen & Premium Finish
-  Long-Lasting Durability

IDEAL USE AREAS




EXTERIOR
WALLS OF
HOMES



APARTMENTS
AND
BUNGALOWS



HOTELS,
PREMIUM &
RESIDENTIAL
BUILDINGS



HOSPITALS,
SCHOOLS &
COMMERCIAL
BUILDINGS

SURFACE PREPARATION & APPLICATION GUIDE



WALLS

NEW SURFACES

- Allow freshly plastered surfaces to cure completely
- Ensure surface is clean, dry and free from dust, grease or loose particles

PREVIOUSLY PAINTED SURFACES

- Remove loose paint by scraping or wire brushing
- Clean thoroughly to remove dust or chalking
- For chalky surfaces, apply 1-2 coat of Jewell Waterborne Exterior Primer before painting



POST CARE

Allow 7 days for full cure. Clean tools with soap and water after use.

EXTERIOR WALLS OF HOMES, PREMIUM RESIDENTIAL AND COMMERCIAL BUILDINGS



MAINTENANCE

Wipe surfaces with a soft cloth and mild detergent. Avoid abrasive cleaners.

TECHNICAL SPEC.

Finish	Rich Sheen
Application	Brush Roller Spray
Dilution	Up to 40% with clean water
Drying Time	4 hours
Coats	2 Coats Recommended
Coverage	110-130 sq.ft/ltr on well-prepared & primed surface (2 coats)
Usage	Exterior only. Stir before use
VOC	Low/meets global standards
Fire Safety	Non-Flammable
Pack Sizes	1Ltr, 4Ltr, 10Ltr & 20Ltr

GENERIC NAME: PAINT

SHADE NAME:

MRP ₹

Incl. of all taxes:

USP ₹

Incl. of all taxes :

BATCH NO.

& MFG DT:

SHELF-LIFE: 36 MONTHS

Lead contents do not exceed 90 parts per million



OZELLCOONER



Regd. Office: **OZELL COONER LTD., 33 / 33A, 3rd Floor,**
Rama Road, Shivaji Marg, Najafgarh Road, Industrial Area,
New Delhi - 110015, India. For query & feedback contact
customer care helpdesk: Call +91 8010105000 or Email:
info@jewellpaints.com or login at : www.jewellpaints.com

The Jewell Brand, Design & logo, are Registered Trademark, of the Ozell Cooner Ltd. **WARNING:** imitation of graphics is a punishable offence. ® =Reg. tm. of Ozell Cooner Ltd. **Keep Out Of Reach Of Children. Protect From Freezing.** Refer to MSDS for additional health & safety information.